NSN 5905-00-917-7311

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-917-7311 **Section Quantity: Body Style:** Cylindrical servo mounted **Pilot Diameter:** Between 0.96830 inches and 0.96880 inches Pilot Length: Between 0.49950 inches and 0.50000 inches **Overall Length:** 3.250 inches **Undercut Width:** 0.06200 inches **Body Diameter:** 1.072 inches **Shaft Diameter:** Between 0.1244 inches and 0.1249 inches **Body Length:** 2.600 inches **Overall Diameter:** 1.092 inches **Mounting Lip Diameter:** 1.06200 inches **Mounting Lip Depth:** 0.06200 inches **Shaft Style:** Round **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.75 inch-ounces **Shaft End Play:** 0.00500 inches **Shaft Runout:** 0.001 inches **Shaft Radial Play:** 0.001 inches **Terminal Location:** Rear end

Mounting Method: Clamp ring

NSN 5905-00-917-7311

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.035/+0.035 single section
Function Conformity Per Section:
Single section terminal base linearity
Fixed Tap Quantity Per Section:
1 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0