## NSN 5905-00-917-7314

**Section Quantity:** 

Cylindrical servo mounted **Reliability Indicator:** 

**Body Style:** 

Not established

2

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-917-7314

Not established
Pilot Diameter:
Between 1.54200 inches and 1.56200 inches
Pilot Length:
Between 0.05700 inches and 0.06700 inches
Overall Length:
3.070 inches
Terminal Length:
0.470 inches
First Flat Length:
Between 0.720 inches and 0.780 inches
Undercut Diameter:
1.620 inches
Undercut Width:
0.07300 inches
Body Diameter:
Between 1.690 inches and 1.750 inches
Shaft Diameter:
Between 0.2494 inches and 0.2497 inches
Shaft Length:
Between 1.410 inches and 1.470 inches
Body Length:
1.600 inches
Overall Diameter:
2.220 inches
Mounting Lip Diameter:
Between 1.74500 inches and 1.75500 inches
Mounting Lip Depth:
Between 0.08800 inches and 0.09800 inches
Shaft Style:
Round, v flatted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 294.0 and 306.0
Maximum Stop Torque:
160.00 inch-ounces

## NSN 5905-00-917-7314

Precision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
2.000 percent, rated amperes c and better industrial clears
Tap Location From Ccw Terminal Per Section In Deg Of Effective Electrical Rotation:
150.0 2nd section
Rotary Actuator Travel In Angular Deg:
340.0
Function Conformity Tolerance Per Section:
-0.50/+0.50 single section
Power Dissipation Rating Per Section In Watts:
1.25 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 2nd section
Tap Location Tolerance Per Section:
-3.0/+3.0 degrees angular rotation all sections
Resistance Tolerance Per Section In Percent:
-2.0/+2.0 all sections
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Special Features:
Decks to be in phase within 1 pct, 1 watt at 221 degrees f
Terminal Type And Quantity:
8 turret
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A002a0