

View Online at <https://aerobasegroup.com/nsn/5905-00-917-7719>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

0.922 inches

**Shaft Diameter:**

0.265 inches

**Shaft Length:**

0.875 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

1.141 inches

**Undercut Diameter:**

0.187 inches

**Shaft Style:**

Round, stepped

**Switch Type:**

Rotary

**Switch Voltage Rating In Volts:**

120.0

**Actuator Type:**

Dual concentric

**Maximum Starting Torque:**

6.00 inch-ounces

**Maximum Running Torque:**

6.00 inch-ounces

**Maximum Stop Torque:**

48.00 inch-ounces

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

0.438 inches

**Switch Operating Position:**

Start of rotation

**Switch Contact Arrangement:**

Double pole, single throw, normally open

**Undercut Length:**

0.375 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear-bottom

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

470.0 ohms c and better industrial clears

**Rotary Actuator Travel In Angular Deg:**

Between 292.0 and 298.0

**Power Dissipation Rating Per Section In Watts:**

0.5 7th secondary finish

**Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 all sections

**Actuator Travel Control Feature:**

Stops

**Switch Current Type And Rating In Amps:**

3.000 ac

**Standard Taper Curve Per Section:**

O 2nd section

**Terminal Type And Quantity:**

10 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0