Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-917-9215

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

1.062 inches

#### Shaft Diameter:

0.125 inches

#### Shaft Length:

0.436 inches

### Mounting Bushing Length:

0.250 inches

#### Body Length:

0.109 inches

# Shaft Style:

Round

# Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

305.0

### Screw Thread Diameter:

0.250 inches

### **Screw Thread Series Designator:**

Unef

### Screw Thready Qty Per Inch (tpi):

20.0

### **Terminal Location:**

Radially positioned over less than half the circumference

#### Mounting Method:

Standard bushing

#### **Features Provided:**

Nonmetallic shaft

### **Electrical Resistance Per Section:**

0.15 ohms single section

### **Rotary Actuator Travel In Angular Deg:**

290.0

# Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

65.0 single section

# Power Dissipation Rating Per Section In Watts:

1.0 free air single section



### **Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

### Actuator Travel Control Feature:

Stops

#### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0