NSN 5905-00-917-9373

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-917-9373

Electrical Resistance: 1.740 ohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Include Tempurature Range of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Include Method: Incapsulated Reliability Indicator: Vot established 30dy Diameter: 1.0250 inches 30dy Length: 1.0250 inches 30dy Length: 1.0251 free air 38yle Designator: Avial terminal each end Fest Data Document: 181349-mill(33/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Vota District Measure: - Demilitarization: No	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 1.0004-1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Tempurature Range Of Tempurature In Deg Celsius At Full Rated Power: 65.0/+145.0 Tempurature Range Of Tempurature In Deg Celsius At Full Rated Power: 66.0/+145.0 Tempurature Range Of Tempurature In Deg Celsius At Full Rated Power: 67.0/+145.0 Tempurature Range Of Tempurature In Deg Celsius: 67.0/+145.0 Tempurature Range Of Tempurature Range Power: 67.0/+145.0 Tempurature Range Of Tempurature Range Power: 67.0/+145.0 Tempurature Range Power Rated Power: 67.0/+145.	-50.0/+50.0
Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 165.0/+145.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 165.0/+145.0 Fempurature Method: 16.0capsulated Ferminal Type: Wire lead Reliability Indicator: 10.250 inches 10.3040 Diameter: 10.250 inches 10.3040 Diameter: 10.250 inches 10.344 inches 10.345 free air 10.345 free air 10.345 free air 10.349-milr33/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, and performance requirements and test conditions that are shown as "typical", "average", ", etc.). 10.150 free Sheft Life: 10	Electrical Resistance:
1.000/41.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/4145.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter: 1.250 inches 30dy Length: 1.344 inches Power Dissipation Rating In Watts: 1.125 free air Style Designator: 1.343 Perminal each end Test Data Document: 1.31349-milrg3/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as 'typical', 'average', '", etc.). Shelf Life: Via Juit Of Measure: - Demilitarization: No	1.740 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: 65.0apsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 1.250 inches	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 noticesure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter: 1.256 inches 30dy Length: 1.344 inches Power Dissipation Rating In Watts: 1.125 free air Style Designator: Availa terminal each end Fest Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Juit Of Measure: - Demilitarization: No	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Enclosure Method: Encapsulated Ferminal Type: Write lead Reliability Indicator: Not established Body Diameter: 10.250 inches Body Length: 10.344 inches Power Dissipation Rating In Watts: 10.125 free air Style Designator: Axial terminal each end Fest Data Document: 191349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Wa Jult Of Measure: - Demilitarization: No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Interport of the property of t	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 nclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established 30dy Diameter: 10.250 inches 30dy Length: 10.344 inches Power Dissipation Rating In Watts: 10.125 free air Style Designator: Axial terminal each end Test Data Document: 81349-mility3/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating in Watts: 0.125 free air Style Designator: Xxial terminal each end Fest Data Document: 81349-mility3/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", **, etc.). Shelf Life: V/a Juit Of Measure:	145.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 3ody Diameter: 0.250 inches 3ody Length: 0.344 inches Power Dissipation Rating in Watts: 0.125 free air Style Designator: Avial terminal each end Fest Data Document: 11349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: V/a Unit Of Measure: - Demilitarization: No	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Avial terminal each end Fest Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Juit of Measure: - Demilitarization: No	-65.0/+145.0
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Jinit Of Measure: - Demilitarization:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Relyle Designator: Axial terminal each end Fest Data Document: 81349-milir93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Juit Of Measure: - Demilitarization: No	Encapsulated
Reliability Indicator: Not established Body Diameter: D. 250 inches Body Length: D. 344 inches Power Dissipation Rating In Watts: D. 125 free air Style Designator: Axial terminal each end Fest Data Document: B1349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Terminal Type:
Note established 30dy Diameter: 10.250 inches 30dy Length: 10.344 inches Power Dissipation Rating In Watts: 10.125 free air Style Designator: Axial terminal each end Fest Data Document: 13.349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). 35helf Life: No 10.110 Measure: 10.110 Measure: 10.110 Measure: 10.110 Measure: 10.110 Measure: 10.1111 Me	Wire lead
Body Length: 0.250 inches Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Fest Data Document: 0.349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Juit Of Measure: Demilitarization:	Reliability Indicator:
2.250 inches 3.30dy Length: 2.344 inches 2.344 inches 2.344 inches 2.345 gree air 3.549 Designator: 3.349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). 3.5461f Life: 3.747 3.758 3.759	Not established
Body Length: 0.344 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Body Diameter:
20.344 inches Power Dissipation Rating In Watts: 20.125 free air Style Designator: Axial terminal each end Fest Data Document: 20.349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: No Demilitarization:	0.250 inches
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization:	Body Length:
2.125 free air Style Designator: Axial terminal each end Fest Data Document: B1349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization:	0.344 inches
Axial terminal each end Test Data Document: 31349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end Fest Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	0.125 free air
Fest Data Document: 81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization:	Style Designator:
B1349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: - Demilitarization:	81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life: N/a Jnit Of Measure: - Demilitarization:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
√a Jnit Of Measure: - Demilitarization:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: - Demilitarization:	Shelf Life:
- Demilitarization:	N/a
No	Unit Of Measure:
No	
	Demilitarization:
Filg:	No
	Fiig:
A001a0	A001a0