

View Online at <https://aerobasegroup.com/nsn/5905-00-917-9705>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.969 inches

**Body Diameter:**

0.922 inches

**Shaft Diameter:**

0.250 inches

**Shaft Length:**

0.875 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.891 inches

**Overall Diameter:**

2.000 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Sleeve

**Switch Type:**

Rotary

**Switch Voltage Rating In Volts:**

125.0

**Actuator Type:**

Single shaft

**Switch Operating Position:**

Start of rotation

**Switch Contact Arrangement:**

Double pole, single throw, one open, one closed

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thread Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear-bottom

**Mounting Method:**

Standard bushing

**Features Provided:**

Switch

**Electrical Resistance Per Section:**

50.0 ohms single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

85.0 single section

**Power Dissipation Rating Per Section In Watts:**

2.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0/+10.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

55.0 single section

**Switch Current Type And Rating In Amps:**

3.000 ac

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

7 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0