## NSN 5905-00-918-0491

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-918-0491 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Body Diameter:** 1.094 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.531 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.156 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Maximum Starting Torque:** 12.00 inch-ounces **Maximum Running Torque:** 1.00 inch-ounces **Maximum Stop Torque:** 192.00 inch-ounces **Nonturn Device Location:** At 12 oclock **Nonturn Device Radius:** 0.500 inches **End Application:** Submarine ship control and navigation systems, sturgeon class ssn (637), submarine antenna, submarine navigation systems, ship, ohio class ssn (trident) **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** 

32.0

Unef

**Terminal Location:** 

Screw Thready Qty Per Inch (tpi):

Radially positioned over less than half the circumference

NSN 5905-00-918-0491 Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Locking bushing
Electrical Resistance Per Section:
50.0 ohms all sections
Rotary Actuator Travel In Angular Deg:
300.0
Resistance Tempurature Characteristic Range Per Section In Percent:
-0.0/+4.5 -55 degrees celsius all sections and +0.0/+2.5 -25 degrees celsius all sections and +0.0/+1.5 0 degrees celsius all sections and
1.5/+1.5 85 degrees celsius all sections and +0.0/+3.5 120 degrees celsius all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
20.0 all sections
Power Dissipation Rating Per Section In Watts:
2.5 free air all sections
Fixed Tap Quantity Per Section:
all sections
Tap Location Tolerance Per Section:
1.0/+1.0 ohms all sections
Resistance Tolerance Per Section In Percent:
10.0/+10.0 all sections
Actuator Travel Control Feature:
Stops
Criticality Code Justification:
Feat
Tap Location From Ccw Terminal Per Section In Ohms:
25.0 all sections
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Special Features:
Veapon system essential
Ferminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
No
Fiig:
A002a0