NSN 5905-00-918-0492

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-918-0492 **Section Quantity:** 2 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** 1.8750 inches Pilot Length: 0.0620 inches **Overall Length:** 2.960 inches **Undercut Diameter:** 1.875 inches **Undercut Width:** 0.0730 inches **Body Diameter:** 2.000 inches **Shaft Diameter:** Between 0.2494 inches and 0.2499 inches **Shaft Length:** 0.700 inches **Body Length:** 2.250 inches **Overall Diameter:** 2.223 inches **Mounting Lip Diameter:** 2.0000 inches **Mounting Lip Depth:** 0.0930 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 360.0 **Maximum Starting Torque:**

Maximum Running Torque: 2.00 inch-ounces

2.00 inch-ounces

NSN 5905-00-918-0492

Precision Wire Wound Variable Resistor - Page 2 of 2



Shaft End Play:
0.005 inches
Shaft Runout:
0.002 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.0015 inches
Shaft Radial Play:
0.001 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Clamp ring
Electrical Resistance Per Section:
10.0 kilohms all sections
Rotary Actuator Travel In Angular Deg:
360.0
Function Conformity Tolerance Per Section:
-0.15/+0.15 all sections
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 all sections
Power Dissipation Rating Per Section In Watts:
0.5 free air all sections
Function Conformity Per Section:
All sections absolute conformity
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 all sections
Actuator Travel Control Feature:
Continuous motion
Function Characteristic Per Section:
All sections 360 degrees sine-cosine
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 all sections
Terminal Type And Quantity:
12 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:

A002a0