NSN 5905-00-918-0495

Section Quantity:

Body Style:

Stops

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-918-0495

Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
0.719 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.812 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.500 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
300.0
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
250.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Power Dissipation Rating Per Section In Watts:
0.25 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:

NSN 5905-00-918-0495

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Por
--

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

2 tab, solder lug and 1 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0