NSN 5905-00-918-2264

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-918-2264 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.310 inches **Overall Height:** 0.310 inches **Overall Width:** 0.220 inches **Mounting Hole Diameter:** 0.087 inches **Shaft Diameter:** 0.100 inches **Shaft Length:** 0.060 inches **Body Length:** 1.250 inches **Body Width:** 0.220 inches **Body Height:** 0.310 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 8.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** 1.000 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole

Features Provided: Nonmetallic shaft **Electrical Resistance Per Section:**

2.000 kilohms single section

NSN 5905-00-918-2264

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

135.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-0.010/+0.010 single section

Power Dissipation Rating Per Section In Watts:

0.8 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0