## NSN 5905-00-918-7468

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-918-7468

· · · · · · · · · · · · · · · · · · ·
Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Overall Length:
0.891 inches
Body Diameter:
0.969 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.375 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.516 inches
Overall Diameter:
1.562 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Actuator Type:
Single shaft
Nonturn Device Location:
At 9 oclock
Nonturn Device Radius:
0.438 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:

500.0 kilohms single section

## NSN 5905-00-918-7468

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



∆mhiant '	Tamnuratura l	In Daa Caleiu	e Par Saction	At Zara Para	ent Rated Power:
	i cilipulatule i	ili Deg Gelsiu	3 1 61 06611011	AL ZOIO I CIU	enii Naicu i Owen.

85.0 single section

**Power Dissipation Rating Per Section In Watts:** 

0.25 free air single section

**Resistance Tolerance Per Section In Percent:** 

-30.0/+30.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

**Standard Taper Curve Per Section:** 

A single section

**Terminal Type And Quantity:** 

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0