NSN 5905-00-919-0160

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-919-0160 **Section Quantity: Body Style:** Cylindrical **Reliability Indicator:** Not established **Body Diameter:** 0.750 inches **Body Length:** 0.375 inches **Actuator Type:** Flush drive with slot-hole **Maximum Starting Torque:** 10.00 inch-ounces **Maximum Running Torque:** 10.00 inch-ounces **Maximum Stop Torque:** 192.00 inch-ounces **Terminal Location:** Rear end **Mounting Method:** Tab **Electrical Resistance Per Section:** 1.0 percent, rated amperes c and better flooring Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section **Power Dissipation Rating Per Section In Watts:** 3.0 7th secondary quality **Resistance Tolerance Per Section In Percent:** -20.0/+20.0 single section Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 55.0 single section **Standard Taper Curve Per Section:** A single section **Special Features:** Screwdriver slot adjustment **Terminal Type And Quantity:** 2 tab, solder lug Shelf Life: N/a

__

Unit Of Measure:

NSN 5905-00-919-0160

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0