Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-919-1777

## Section Quantity:

1

Body Style:

Cylindrical bushing mounted

## **Reliability Indicator:**

Not established

#### **Body Diameter:**

0.969 inches

#### Shaft Diameter:

0.250 inches

#### Shaft Length:

0.875 inches

## Mounting Bushing Length:

0.375 inches

#### Body Length:

## 0.500 inches

Shaft Style:

#### Round

Actuator Type:

Single shaft

## Effective Electrical Rotation In Deg Angular Rotation:

300.0

#### Nonturn Device Location:

At 9 oclock

#### **Nonturn Device Radius:**

0.438 inches

#### Screw Thread Diameter:

0.375 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# **Terminal Location:**

Radially positioned over less than half the circumference

# Mounting Method:

Standard bushing

# **Electrical Resistance Per Section:**

5.0 kilohms single section

# Rotary Actuator Travel In Angular Deg:

300.0

# Power Dissipation Rating Per Section In Watts:

4.0 free air single section

AeroBase Group

**Resistance Tolerance Per Section In Percent:** 

-10.0/+10.0 single section

#### Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0