NSN 5905-00-919-3145

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-919-3145

1.250 ohms Resistance Tolerance In Percent: -3.000/+3.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: -1.500 inches Body Diameter: Between 0.125 inches and 0.250 inches Body Length: Between 0.459 inches and 0.250 inches Body Length: 2.50 own 0.459 inches and 0.531 inches Power Dissipation Rating In Watts: -3.000 free air Cubic Measure (non-core): -0.026 cubic inches Unpackaged Unit Weight: -2.5 grams Style Designator: Awial terminal each end Test Data Document: 80103-din13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Lite: No Unit of Measure: Demilitarization: No Fig: House Amanufacture of Ama	Electrical Resistance:
3.00043.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diamete: Between 0.125 inches and 0.250 inches Body Diamete: Between 0.125 inches and 0.531 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: B0103-din13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing; Sheft Life: Na Unit Of Measure:	1.250 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 355.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.459 inches and 0.250 inches Body Diameter: Between 0.459 inches and 0.531 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.226 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: Bottowen of 150 fordrawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. Sheft Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 30.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.125 inches and 0.250 inches Body Diameter: Between 0.125 inches and 0.250 inches Body Length: Between 0.469 inches and 0.531 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Style Designator: Axial terminal each end Test Data Document: 810103-dfin13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing). Shelf Life: N/a Unit of Measure:	-3.000/+3.000
Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 350.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.125 inches and 0.250 inches Body Diameter: Between 0.125 inches and 0.250 inches Body Length: Between 0.469 inches and 0.531 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfin13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
aso.0 Inclosure Method: Encaspulated Terminal Type: Wrire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.125 inches and 0.250 inches Body Length: Between 0.469 inches and 0.531 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Sheff Life: Na Unit Of Measure:	25.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.125 inches and 0.250 inches Body Length: Between 0.459 inches and 0.531 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.125 inches and 0.250 inches Body Length: Between 0.459 inches and 0.531 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Avial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure:	350.0
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.125 inches and 0.250 inches Body Length: Between 0.469 inches and 0.531 inches Power Dissipation Rating in Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Style Designator: Axial terminal each end Test Data Document: 80103-dfm13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: V/a Unit Of Measure:	Inclosure Method:
Wire lead Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.125 inches and 0.250 inches Body Length: Between 0.469 inches and 0.531 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	Encapsulated
Reliability Indicator: Not established Terminal Length: 1.500 inches Body Diameter: Between 0.125 inches and 0.250 inches Body Length: Between 0.469 inches and 0.531 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-6111-3051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	Terminal Type:
Note stablished Terminal Length: 1.500 inches Body Diameter: Between 0.125 inches and 0.250 inches Body Length: Between 0.469 inches and 0.531 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Na Unit Of Measure: Demilitarization: No Fig:	Wire lead
Terminal Length: 1.500 inches Body Diameter: Between 0.125 inches and 0.250 inches Body Length: Between 0.469 inches and 0.531 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fig:	Reliability Indicator:
1.500 inches Body Diameter: Between 0.125 inches and 0.250 inches Body Length: Between 0.469 inches and 0.531 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Between 0.125 inches and 0.250 inches Body Length: Between 0.469 inches and 0.531 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Terminal Length:
Between 0.125 inches and 0.250 inches Body Length: Between 0.469 inches and 0.531 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	1.500 inches
Between 0.469 inches and 0.531 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
Between 0.469 inches and 0.531 inches Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.125 inches and 0.250 inches
Power Dissipation Rating In Watts: 3.000 free air Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
3.000 free air Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.469 inches and 0.531 inches
Cubic Measure (non-core): 0.026 cubic inches Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Power Dissipation Rating In Watts:
Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	3.000 free air
Unpackaged Unit Weight: 2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Cubic Measure (non-core):
2.5 grams Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.026 cubic inches
Style Designator: Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Unpackaged Unit Weight:
Axial terminal each end Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	2.5 grams
Test Data Document: 80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	80103-dfn13-051 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
N/a Unit Of Measure: Demilitarization: No Fiig:	etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0