Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-919-3178

# Section Quantity:

1

Body Style:

Cylindrical

### Reliability Indicator:

Not established

### Body Diameter:

0.770 inches

### Body Length:

0.438 inches

### Actuator Type:

Flush drive with slot-hole

### Effective Electrical Rotation In Deg Angular Rotation:

248.0

#### **Terminal Location:**

### Rear end

Mounting Method:

Tab

### Features Provided:

Grounded contact arm

#### **Electrical Resistance Per Section:**

15.0 kilohms single section

### Rotary Actuator Travel In Angular Deg:

250.0

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 single section

### Power Dissipation Rating Per Section In Watts:

2.0 free air single section

### **Resistance Tolerance Per Section In Percent:**

-20.0/+20.0 single section

### Actuator Travel Control Feature:

Stops

### Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

# Standard Taper Curve Per Section:

A single section

# Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

### Unit Of Measure:

---

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A002a0