NSN 5905-00-919-6022

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-919-6022

Section Quantity:
1
Body Style:
Rectangular w/bushing
Reliability Indicator:
Not established
Shaft Diameter:
0.125 inches
Shaft Length:
0.250 inches
Mounting Bushing Length:
0.250 inches
Body Length:
1.062 inches
Body Width:
0.250 inches
Body Height:
0.312 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Screw Thread Diameter:
0.190 inches
Screw Thread Series Designator:
Unf
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear end
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
5400.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-50.0/+50.0 single section

1.0 free air single section

Power Dissipation Rating Per Section In Watts:

NSN 5905-00-919-6022

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-5.0/+5.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No