NSN 5905-00-919-6255

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-919-6255

Electrical Resistance: 8384.000 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Akial terminal each end Test Data Document: 81349-miliz26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: No Demilitarization: No Filig:	
Electrical Resistance: 634.000 ohms Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Realiability Indicator: Not established Body Diameter: -0.312 inches Body Langth: -0.375 inches Power Dissipation Rating in Watts: -5.000 free air Style Designator: Axial terminal each end Tests Data Document: 81349-mili28/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: No Publificatization: No Filig:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: -1.000/4-1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wive lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: No Unit Of Measure: — Demilitarization: No Filig:	-30.0/+30.0
Resistance Tolerance in Percent: -1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating in Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: No Unit Of Measure:	Electrical Resistance:
Anbient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milizent Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure:	634.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.04-275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, inclustry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 8x1349-milr28/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: N/a Unit Of Measure:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Tests Data Document: 81349-milit28/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.): Shelf Life: N/a Unit of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wife lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.312 inches Body Length: 10.875 inches Power Dissipation Rating In Watts: 15.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-miltr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit of Measure: Demilitarization: No Fiig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milit26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	275.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Rediability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-miliz6/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	-55.0/+275.0
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Method:
Wire lead Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Terminal Type:
Note stablished Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Wire lead
Body Diameter: 0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Reliability Indicator:
0.312 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Not established
Body Length: 0.875 inches Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Diameter:
Dower Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.312 inches
Power Dissipation Rating In Watts: 5.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Body Length:
Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.875 inches
Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	5.000 free air
Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Unit Of Measure: Demilitarization: No Filig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0