NSN 5905-00-919-8334

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-919-8334

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Mounting Hole Diameter:
0.120 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.750 inches
Body Length:
6.000 inches
Body Width:
0.750 inches
Body Height:
1.000 inches
Shaft Style:
Round
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
360.0
Screw Thread Diameter:
0.112 inches
Screw Thread Series Designator:
Unc
Screw Thready Qty Per Inch (tpi):
28.0
Mounting Facility Quantity:
4
Terminal Location:
Left adjacent side two rows
Mounting Method:
Threaded hole
Electrical Resistance Per Section:
2.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
475 O single postion

175.0 single section

NSN 5905-00-919-8334

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -25.0/+25.0 single section Power Dissipation Rating Per Section In Watts: 2.5 free air single section Resistance Tolerance Per Section In Percent: -5.0/+5.0 single section Actuator Travel Control Feature: Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

Standard Taper Curve Per Section:

A single section

40.0 single section

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0