

View Online at <https://aerobasegroup.com/nsn/5905-00-919-8613>

Section Quantity:

3

Body Style:

Rectangular bushing mounted

Reliability Indicator:

Not established

Overall Length:

1.969 inches

Overall Width:

0.625 inches

Shaft Diameter:

0.250 inches

Shaft Length:

0.625 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.344 inches

Body Width:

0.625 inches

Body Height:

0.625 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

260.0

Maximum Starting Torque:

3.50 inch-ounces

Maximum Running Torque:

3.50 inch-ounces

Maximum Stop Torque:

64.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.305 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

1.0 megohms all sections

Rotary Actuator Travel In Angular Deg:

300.0

Resistance Temperature Characteristic Range Per Section In Percent:

+0.0/+6.0 -55 degrees celsius all sections and +0.0/+5.0 120 degrees celsius all sections

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

120.0 all sections

Power Dissipation Rating Per Section In Watts:

0.5 free air all sections

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0