## NSN 5905-00-920-8974

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-00-920-8974

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 1.5615 inches and 1.5625 inches
Pilot Length:
Between 0.0590 inches and 0.0650 inches
Overall Length:
2.500 inches
First Flat Length:
Between 0.490 inches and 0.510 inches
Flat Height:
Between 0.180 inches and 0.200 inches
Undercut Diameter:
1.562 inches
Undercut Width:
Between 0.0760 inches and 0.0810 inches
Body Diameter:
Between 1.800 inches and 1.820 inches
Angle Of Mounting Hole In Deg:
60.0
Angle Between Centerlines Of Mounting Holes In Deg:
120.0
Shaft Diameter:
0.249 inches
Shaft Length:
Between 0.745 inches and 0.755 inches
Body Length:
Between 1.740 inches and 1.760 inches
Overall Diameter:
2.500 inches
Mounting Lip Diameter:
Between 1.8000 inches and 1.8200 inches
Mounting Lip Depth:
Between 0.0590 inches and 0.0650 inches
Mounting Hole/stud Circle Diameter:
1.250 inches
Shaft Style:

Round, flatted

## NSN 5905-00-920-8974

Precision Wire Wound Variable Resistor - Page 2 of 3



## **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 1440.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.40 inch-ounces **Maximum Stop Torque:** 500.00 inch-ounces **Screw Thread Diameter:** 0.138 inches **Screw Thread Series Designator:** Unc Screw Thready Qty Per Inch (tpi): **Mounting Facility Quantity: Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Threaded hole **Electrical Resistance Per Section:** 1.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 1440.0 **Function Conformity Tolerance Per Section:** -0.01/+0.01 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 2.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Stops **Function Characteristic Per Section:**

Single section linear

Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:

-20.0/+20.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

## NSN 5905-00-920-8974

Precision Wire Wound Variable Resistor - Page 3 of 3



Terminal Type And Quantity:
3 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0