NSN 5905-00-921-4702

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-921-4702 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established liilength: 0.562 inches **Body Diameter:** 0.625 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.437 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.500 inches liidiameter: 0.625 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** 0.375 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

2.000 kilohms single section

Power Dissipation Rating Per Section In Watts:

0.3 free air single section

NSN 5905-00-921-4702

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Terminal Type And Quantity:

3 tab, solder lug

.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0