## NSN 5905-00-921-4826

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-921-4826

Electrical Resistance: 398.000 ohms Resistance Tolerance In Percent: 4,1000/41,000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 27.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/±275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0,1687 inches Body Length: 0,1690 inches Power Dissipation Rating In Watts: 3,000 free air Style Designator: 4,4441 terminal each end Test Data Document: 191349-milize/is specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit of Measure: — Demilitarization: No	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 1.0004-1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Avail terminal each end Test Dan Document: Bridden Bridge Specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure:	-30.0/+30.0
Resistance Tolerance In Percent:  1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power:  25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:  275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Body Diameter:  0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts:  3.000 free air Style Designator: Axial terminal each end Test Data Document:  8xive Designator: Axial terminal each end Test Data Document:  9xive Output:  9xive Designator: Axial terminal each end Test Data Document:  9xive Designator: Axial terminal each end Test Data Document:  9xive Designator: Axial terminal each end Test Data Document:  9xive Designator: Axial terminal each end Test Data Document:  9xive Designator: Axial terminal each end Test Data Document:  9xive Designator: Axial terminal each end Test Data Document:  9xive Designator: Axial terminal each end Test Data Document:  9xive Designator: Axial terminal each end Test Data Document:  9xive Designator: Axial terminal each end Test Data Document:  10xive Designator: Axial terminal each end Test Data Document:  10xive Designator: Axial terminal each end Test Data Document:  10xive Designator: Axial terminal each end Test Data Document:  10xive Designator: Axial terminal each end Test Data Document:  10xive Designator: Axial terminal each end Test Data Document:  10xive Designator: Axial terminal each end Test Data Document:  10xive Designator: Axial terminal each end Test Data Document:  10xive Designator: Axial terminal each end Test Data Document:  10xive Designator Axial terminal each end Test Data Document:  10xive Designator Axial terminal each end Test Data Document:  10xive Designator Axial terminal each end Test Data Document:  10xive Designator Axial terminal each end Test Data Designator Axial terminal each end Test Data Designation Axial terminal each end Test Data Designation Test Data Designation Test	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.1487 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 31349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Unit of Measure:	698.000 ohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 255.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 20.187 inches Body Length: 20.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Avial terminal each end Test Data Document: 31349-milir26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wire United Of Measure:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4275.0  Inclosure Method: Encapsulated  Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 20.187 inches Body Length: 20.560 inches Power Dissipation Rating In Watts: 30.00 free air Style Designator: Availa terminal each end Test Data Document: 31349-milit 26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: W/a  Unit of Measure:	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.). Shelf Life: Wa Unit Of Measure:	Ambient Tempurature In Deg Celsius At Full Rated Power:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: -0.187 inches Body Length: -0.560 inches Power Dissipation Rating In Watts: -0.300 free air Style Designator:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  155.0/+275.0  Inclosure Method: Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  10.187 inches  Body Length:  10.560 inches  Power Dissipation Rating In Watts:  13.000 free air  Style Designator:  Avail terminal each end  Test Data Document:  13149-mili26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; accludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:  No	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: Bridden Englished (Includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: No Unit Of Measure: Demilitarization: No	275.0
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.560 inches Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-mili26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated  Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.187 inches  Body Length:  0.560 inches  Power Dissipation Rating In Watts:  3.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No	-55.0/+275.0
Terminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No	Inclosure Method:
Wire lead  Reliability Indicator:  Not established  Body Diameter: 0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No	Encapsulated
Reliability Indicator:  Not established  Body Diameter:  0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:	Terminal Type:
Note stablished  Body Diameter:  D.187 inches  Body Length: D.560 inches  Power Dissipation Rating In Watts:  3.000 free air  Style Designator:  Axial terminal each end  Test Data Document:  B1349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Unit Of Measure:  Demilitarization:  No	Wire lead
Body Diameter:  0.187 inches  Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Reliability Indicator:
2.187 inches  Body Length: 2.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Not established
Body Length: 0.560 inches  Power Dissipation Rating In Watts: 3.000 free air  Style Designator: Axial terminal each end  Test Data Document: B1349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure:  Demilitarization:	Body Diameter:
Power Dissipation Rating In Watts: 3.000 free air Style Designator: Axial terminal each end Test Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure:	0.187 inches
Power Dissipation Rating In Watts: 3.000 free air  Style Designator:  Axial terminal each end  Test Data Document: 31349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  W/a  Unit Of Measure:  Demilitarization:	Body Length:
Style Designator:  Axial terminal each end  Test Data Document:  B1349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	0.560 inches
Style Designator:  Axial terminal each end  Test Data Document:  81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  B1349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:	3.000 free air
Test Data Document:  81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No	Style Designator:
B1349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:	81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a Unit Of Measure: Demilitarization: No	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Unit Of Measure: Demilitarization:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Unit Of Measure: Demilitarization:	Shelf Life:
 Demilitarization: No	N/a
No	Unit Of Measure:
No	<del></del>
	Demilitarization:
Filiq:	No
	Fiig:
A001a0	A001a0