NSN 5905-00-922-4853

Section Quantity:

Reliability Indicator:

Not established

Overall Length:

Rectangular w/mounting holes

Body Style:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-922-4853

0.712 inches
Terminal Length:
0.172 inches
Overall Height:
Between 0.490 inches and 0.510 inches
Overall Width:
Between 0.180 inches and 0.230 inches
Shaft Diameter:
Between 0.058 inches and 0.098 inches
Shaft Length:
0.045 inches
Body Length:
0.540 inches
Body Width:
Between 0.180 inches and 0.230 inches
Body Height:
Between 0.490 inches and 0.510 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Maximum Running Torque:
5.00 inch-ounces
Center To Center Distance Between Terminals:
Between 0.090 inches and 0.110 inches
Lateral Distance Between Mounting Hole Centers:
0.419 inches
Terminal Location:
Lower adjacent side single row
Mounting Method:
Terminal
Electrical Resistance Per Section:
5.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
Between 7200.0 and 16200.0

NSN 5905-00-922-4853

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Center 7	To Ce	nter I	Distance	Between	Center	Termina	I And	Outside '	Terminal:

Between 0.090 inches and 0.110 inches

Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

0.75 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Continuous motion

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

85.0 single section

Test Data Document:

81349-mil-r-27208-4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity	Termin	al Type	And C	Quantity	/ :
----------------------------	--------	---------	-------	----------	------------

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0