NSN 5905-00-922-6544

Film Fixed Resistor - Page 1 of 1

A001a0



View Online at https://aerobasegroup.com/nsn/5905-00-922-6544

Tempurature Coefficient Of Resistance in Ppm Per Deg Celsius: 200.0/4200.0 Electrical Resistance: 1.620 kilohms Resistance Tolerance In Percent: 1.000/41.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/470.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11283-5-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "hoical", "average", "", etc.).	Computed use Coefficient Of Resistance In Dam Des Des Calaines
Electrical Resistance: 1.620 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.287 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Akaila terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Resistance Tolerance In Percent: -1.000/41.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Critticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Ambient Tempurature In Deg Celsius At Full Rated Power: 70.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.0287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.3875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+70.0 Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Inclosure Method: Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
Hermetically sealed Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	55.0/+70.0
Terminal Type: Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	nclosure Method:
Wire lead Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Hermetically sealed
Reliability Indicator: Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Ferminal Type:
Established Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Vire lead
Reliability Failure Rate Level In Percent: 0.0003 Body Diameter: 0.287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Reliability Indicator:
Body Diameter: 0.287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Established
Body Diameter: 0.287 inches Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Reliability Failure Rate Level In Percent:
Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	0.0003
Body Length: 0.875 inches Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Body Diameter:
Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	0.287 inches
Power Dissipation Rating In Watts: 0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Body Length:
0.750 free air Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	0.875 inches
Criticality Code Justification: Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Power Dissipation Rating In Watts:
Test Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	0.750 free air
Style Designator: Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Criticality Code Justification:
Axial terminal each end Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	- est
Test Data Document: 11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Style Designator:
11293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Axial terminal each end
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Fest Data Document:
	1293-35-267420 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.)	ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:	Shelf Life:
N/a	N/a
Unit Of Measure:	Init Of Measure:
	-
Demilitarization:	Demilitarization:
No	No
Fiig:	iig: