## NSN 5905-00-922-6578

Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-922-6578

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
1.531 inches
Shaft Diameter:
0.093 inches
Shaft Length:
0.543 inches
Mounting Bushing Length:
0.325 inches
Body Length:
0.312 inches
Shaft Style:
Round
Actuator Type:
Double ended shaft
Maximum Starting Torque:
0.20 inch-ounces
Maximum Running Torque:
0.20 inch-ounces
Maximum Stop Torque:
1.00 inch-ounces
Shaft End Play:
0.005 inches
Terminal Location:
Radially positioned over less than half the circumference
Electrical Resistance Per Section:
5.0 kilohms single section
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-20.0/+20.0 single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Function Characteristic Per Section:
Single section linear

## NSN 5905-00-922-6578

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Special	Features:
---------	-----------

Front shaft and bushing has a housing-spring, spring and retailer; back shaft has a gear assembly

**Terminal Type And Quantity:** 

4 tab, solder lug

. ....,

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A002a0