

View Online at <https://aerobasegroup.com/nsn/5905-00-922-7040>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

1.329 inches

**Body Diameter:**

1.188 inches

**Shaft Diameter:**

Between 0.2470 inches and 0.2495 inches

**Shaft Length:**

0.625 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.688 inches

**Overall Diameter:**

1.563 inches

**Shaft Style:**

Round, slotted

**Actuator Type:**

Single shaft

**Effective Electrical Rotation In Deg Angular Rotation:**

260.0

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

10.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

300.0

**Function Conformity Tolerance Per Section:**

-0.50/+0.50 single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

200.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.375 free air single section

**Function Conformity Per Section:**

Single section independent linearity

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Stops

**Function Characteristic Per Section:**

Single section linear

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

40.0 single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0