## NSN 5905-00-922-9841

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-922-9841

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -20.0/+20.0  Electrical Resistance: 1.000 kilohms  Resistance Tolerance In Percent: -0.500/+0.500  Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0	
Electrical Resistance:  1.000 kilohms  Resistance Tolerance In Percent: -0.500/+0.500  Ambient Tempurature In Deg Celsius At Full Rated Power:	
1.000 kilohms  Resistance Tolerance In Percent: -0.500/+0.500  Ambient Tempurature In Deg Celsius At Full Rated Power:	
Resistance Tolerance In Percent: -0.500/+0.500 Ambient Tempurature In Deg Celsius At Full Rated Power:	
-0.500/+0.500  Ambient Tempurature In Deg Celsius At Full Rated Power:	
Ambient Tempurature In Deg Celsius At Full Rated Power:	
125.0	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:	
145.0	
Tempurature Range Of Tempurature Coefficient In Deg Celsius:	
-65.0/+145.0	
Inclosure Method:	
Encapsulated	
Terminal Type:	
Wire lead	
Body Diameter:	
0.250 inches	
Body Length:	
0.344 inches	
Power Dissipation Rating In Watts:	
0.125 free air	
Style Designator:	
Axial terminal each end	
Test Data Document:	
81349-milr93/14 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	on format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environ	mental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Shelf Life:	
N/a	
Unit Of Measure:	
<del></del>	
Demilitarization:	
No	
Fiig:	
A001a0	