NSN 5905-00-923-2928

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-923-2928

20.04-20.0 Electrical Resistance: 1.210 kilohms Resistance Tolerance in Percent: 1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 25.0 Fempurature Range Of Tempurature Coefficient in Deg Celsius: 25.0/+35.0 Fempurature Rethod: Encapsulated Ferminal Type: Wife lead Reliability Indicator: Vid established Body Diameter: 2.188 inches Body Length: 2.375 inches Power Dissipation Rating in Watts: 2.000 fee air Rylo Designator: Xikial terminal each end Fest Data Document: 19971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: Via Jint Of Measure:	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 1.0004-1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature Range Of Tempurature In Deg Celsius: 25.0 Ambient Tempurature Range Of Tempurature Rated Power: 25.0 Ambient Tempurature Rated Power: 25.0 Ambient Tempurature Range Of Tempurature Rated Power: 25.0 Ambient Tempu	-20.0/+20.0
Resistance Tolerance in Percent: 1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 25.0.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 25.0/+35.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 25.0/+35.0 Tempurature Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established 30xly Diameter: 20.188 inches 30xly Length: 20.375 inches Power Dissipation Rating in Watts: 20.000 free air 2xyly Designator: Avial terminal each end Test Data Document: 2xyly Designator: Avial terminal each end Test Data Document: 3xyly Designator: Avial terminal each end rest Data Document: 3xyly Designator: Avial terminal each end Test Data Document: 3xyly Designator: 4xyly Desi	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0.435.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0.435.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0.435.0.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0.435.0.0 Tempurature Method: Tempurature Method	1.210 kilohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0.0 Fempurature Range Of Tempurature Coefficient in Deg Celsius: 25.0/4-350.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Feet Data Document: 99971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Julio Of Measure: - Demilitarization: No Elig:	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 550.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 550.0/4350.0 Inclosure Method: Incapsulated Identification (Type: Wire lead Reliability Indicator: Not established Body Diameter: 2.188 inches Body Length: 2.375 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Avail terminal each end Fest Data Document: Desyntherication (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Va Juit Of Measure: - Demilitarization: No	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 150.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 150.0+350.0 Tempurature Method: Tencapsulated Terminal Type: Wire lead Reliability Indicator: Not established 3ody Diameter: 10.188 inches 2ower Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Test Data Document: 199971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Valuation Measure: - Demilitarization: No.	Ambient Tempurature In Deg Celsius At Full Rated Power:
Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+350.0 Inclosure Method: Encapsulated Ferminal Type: Write lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: xixial terminal each end Fest Data Document: 99971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Juit Of Measure: - Demilitarization: No Filig:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4350.0 nclosure Method: ncapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Fest Data Document: 99971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Julit Of Measure: - Demilitarization: No Figig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: D. 188 inches Body Dength: D. 187 inches Power Dissipation Rating In Watts: Reliability Designator: Reliability Indicator: Reliability Designator: Reliability De	350.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: D. 188 inches Body Length: D. 375 inches Power Dissipation Rating In Watts: D. 000 free air Style Designator: Axial terminal each end Fest Data Document: Desprict Ty736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: W/a Juit Of Measure: - Demilitarization: No Filig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Feest Data Document: 99971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: Demilitarization: No Pilig:	-55.0/+350.0
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Fest Data Document: 199971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: Demilitarization: No Perilig:	Inclosure Method:
Action of the lead Reliability Indicator: Not established Body Diameter: 0.188 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.000 free air Style Designator: Axial terminal each end Fest Data Document: 0.9971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: - Demilitarization: No	Encapsulated
Reliability Indicator: Not established Body Diameter: D. 188 inches Body Length: D. 375 inches Power Dissipation Rating In Watts: D. 2000 free air Style Designator: Axial terminal each end Fest Data Document: Description of the commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization: No Demilitarization:	Terminal Type:
Note established Body Diameter: D.188 inches Body Length: D.375 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Avail terminal each end Fest Data Document: Despri-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No	Wire lead
30dy Length: 0.188 inches 30dy Length: 0.375 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Fest Data Document: 99971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Reliability Indicator:
2.0.188 inches 3.30dy Length: 2.0.375 inches 2.0.00 free air 3.5tyle Designator: 3.5ty	Not established
Body Length: 0.375 inches Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Fest Data Document: 0.9971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization: No	Body Diameter:
Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Fest Data Document: 29971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; 29271-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; 29271-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; 29271-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; 29271-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; 29271-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; 29271-7736734 specification t	0.188 inches
Power Dissipation Rating In Watts: 2.000 free air Style Designator: Axial terminal each end Fest Data Document: 99971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Body Length:
2.000 free air Style Designator: Axial terminal each end Fest Data Document: 99971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No Filig:	0.375 inches
Style Designator: Axial terminal each end Fest Data Document: 99971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: - Demilitarization: No Filig:	Power Dissipation Rating In Watts:
Axial terminal each end Fest Data Document: 09971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	2.000 free air
Test Data Document: 09971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: - Demilitarization: No Fig:	Style Designator:
29971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	99971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life: N/a Jnit Of Measure: - Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Jnit Of Measure: - Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: - Demilitarization: No -iig:	Shelf Life:
- Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Filg:	Demilitarization:
	No
000120	Fiig:
100 100	A001a0