## NSN 5905-00-923-8547

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-923-8547

Electrical Resistance: 3.340 ohms Resistance Tolerance In Percent: 1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 ncilosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 300dy Diameter: 0.375 inches 3	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance in Percent: 1.000/4-1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Ambient Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/4275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/4275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter: 0.375 inches 30dy Length: 1.780 inches Power Dissipation Rating in Watts: 10.000 fee air Style Designator: xxival terminal each end Test Data Document: 91349-milit26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "', etc.). Shelf Life: Via Juit Of Measure: — Demilitarization: 1000 1000 1000 1000 1000 1000 1000 10	-50.0/+50.0
Resistance Tolerance in Percent: 1.000/+1.000 Ambient Tempurature in Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 55.0/+275.0 Tempurature Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established 3040 Diameter: 3.375 inches 3040 Length: 1.780 inches Power Dissipation Rating in Watts: 10.000 free air Style Designator: Axial terminal each end Test Data Document: 13494-milizer6 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; xiccludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Via Junit Of Measure:	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0 Tempurature Range Of Tempurature R	6.340 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 25.0+2/75.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reflability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.780 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Axial terminal each end Test Dat Document: 31494-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Sheff Life: Via Juit Of Measure: — Demilitarization: No	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+275.0  Inclosure Method: Incapsulated  Terminal Type:  Wire lead  Reliability Indicator: Not established  Body Diameter: 0.375 inches  Body Diameter: 0.375 inches  Power Dissipation Rating In Watts: 1.780 inches  Power Dissipation Rating In Watts: 1.000 fee air  Style Designator: Axial terminal each end  Test Data Document: 131349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Via  Ditt Of Measure:  Demilitarization: No	-1.000/+1.000
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0  Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/±275.0  Tempurature Method: Encapsulated  Terminal Type: Wire lead  Reliability Indicator: Not established  Body Diameter: 0.375 inches  Body Length: 1.780 inches  Power Dissipation Rating In Watts: 10.000 free air  Style Designator: Avail terminal each end  Test Data Document: 181349-milit 26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).  Shelf Life: No Duit Of Measure: - Demilitarization: No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Prempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/+275.0  nclosure Method: Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator: Not established  Body Diameter: 0.375 inches  Body Length: 1.780 inches  Power Dissipation Rating In Watts: 10.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Ayia  Julit Of Measure:  Demilitarization:  No  Ferilig:	25.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:  55.0/4275.0  nclosure Method:  Encapsulated  Ferminal Type:  Wire lead  Reliability Indicator:  Not established  Body Diameter:  0.375 inches  Body Length:  1.780 inches  Power Dissipation Rating In Watts:  10.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  81349-milt26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Wa  Julit Of Measure:  - Demilitarization:  No  Figig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Diameter: 0.375 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milit26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Wa Juit Of Measure: - Demilitarization: No Filig:	275.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.780 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Jnit Of Measure: - Demilitarization: No Fiig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.780 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Avial terminal each end Fest Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheft Life: Via Juit Of Measure:	-55.0/+275.0
Ferminal Type:  Mire lead  Reliability Indicator:  Not established  Body Diameter:  0.375 inches  Body Length:  1.780 inches  Power Dissipation Rating In Watts:  10.000 free air  Style Designator:  Avial terminal each end  Fest Data Document:  81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  Via  Unit Of Measure:  Demilitarization:  No  Fig:	Inclosure Method:
Are lead  Reliability Indicator: Not established  Body Diameter: 0.375 inches  Body Length: 1.780 inches  Power Dissipation Rating In Watts: 10.000 free air  Style Designator: Avial terminal each end  Fest Data Document: 81349-mill 26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: W/a  Juit Of Measure: - Demilitarization: No  Fig:	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.375 inches Body Length: 1.780 inches Power Dissipation Rating In Watts: 10.000 free air Style Designator: Axial terminal each end Fest Data Document: 81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No	Terminal Type:
Note established  Gody Diameter:  1.780 inches  Power Dissipation Rating In Watts:  10.000 free air  Style Designator:  Avaid terminal each end  Fest Data Document:  18.349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fig:	Wire lead
Body Length:  1.780 inches  Power Dissipation Rating In Watts:  10.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Signification type data in specification format; average", "", etc.).	Reliability Indicator:
D.375 inches Body Length:  1.780 inches Power Dissipation Rating In Watts:  10.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  W/a  Julit Of Measure:  Demilitarization:  No	Not established
Body Length:  1.780 inches  Power Dissipation Rating In Watts:  10.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  W/a  Julit Of Measure:  Demilitarization:  No	Body Diameter:
Power Dissipation Rating In Watts: 10.000 free air Style Designator: Axial terminal each end Fest Data Document: 31349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	0.375 inches
Power Dissipation Rating In Watts:  10.000 free air  Style Designator:  Axial terminal each end  Fest Data Document:  31349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:  No  Fig:	Body Length:
Style Designator: Axial terminal each end Fest Data Document: B1349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life: N/a  Unit Of Measure: Demilitarization: No Filig:	1.780 inches
Style Designator:  Axial terminal each end  Fest Data Document:  31349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Filig:	Power Dissipation Rating In Watts:
Axial terminal each end  Test Data Document:  81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:  No  Fiig:	10.000 free air
Fest Data Document:  81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:  No  Fig:	Style Designator:
31349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Jnit Of Measure:  Demilitarization:  No  Fiig:	Axial terminal each end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Filig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).  Shelf Life:  N/a  Unit Of Measure:  Demilitarization:  No  Fiig:	81349-milr26/5 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
Shelf Life: N/a  Jnit Of Measure: - Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a  Jnit Of Measure:   Demilitarization:  No  Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Filg:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Filg:	Demilitarization:
	No
\001a0	Fiig:
100100	A001a0