NSN 5905-00-924-6706

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-924-6706

Section Quantity:
1
Body Style:
Rectangular w/mounting holes/slots
Reliability Indicator:
Not established
Terminal Length:
0.500 inches
Mounting Hole Diameter:
0.093 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.050 inches
Body Length:
1.250 inches
Body Width:
0.290 inches
Body Height:
0.344 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
8640.0
Center To Center Distance Between Terminals:
0.700 inches
Lateral Distance Between Mounting Hole Centers:
1.000 inches
Mounting Facility Quantity:
2
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Terminal and unthreaded hole
Features Provided:
Hermetically sealed
Electrical Resistance Per Section:
2.0 kilohms single section
Rotary Actuator Travel In Angular Deg:

9720.0

NSN 5905-00-924-6706

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Center To Center Distance Between Center Terminal And Outside Terminal:
0.300 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Precious Material And Location:
Terminals gold
Precious Material:
Gold
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: