## NSN 5905-00-924-9179

Thermal Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-924-9179

Terminal Length: 2.000 inches Body Outside Diameter: 0.660 inches Body Width: 0.060 inches Maximum Power Dissipation Rating: 2.50 watts Ambient Tempurature At Full Rated Power: 2.50 degrees celsius Maximum Operating Temp: 125.0 degrees celsius Thermal Time Constant In Seconds: 80.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 20.0 Inclosure Type: Encapsulated Zero Power Resistance: 5.240 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0 Style Designator: Disk Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Filg:		liability Indicator: t established
2.000 inches Body Outside Diameter: 0.660 inches Body Width: 0.060 inches Maximum Power Dissipation Rating: 2.50 watts Ambient Tempurature At Full Rated Power: 2.50 degrees celsius Maximum Operating Temp: 125.0 degrees celsius Thermal Time Constant In Seconds: 80.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 20.0 Inclosure Type: Encapsulated Zero Power Resistance: 5.240 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0 Style Designator: Disk Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Filg:		
Body Outside Diameter: 0.660 inches Body Width: 0.060 inches Maximum Power Dissipation Rating: 2.50 watts Ambient Tempurature At Full Rated Power: 25.0 degrees celsius Maximum Operating Temp: 125.0 degrees celsius Maximum Operating Temp: 125.0 degrees celsius Thermal Time Constant In Seconds: 80.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 20.0 Inclosure Type: Encapsulated Zero Power Resistance: 5.240 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0 Style Designator: Disk Terminal Type And Quantity: 2 wire lead Sheff Life: N/a Unit Of Measure:  Demilitarization: No Fig:		-
New of the set of the		
Body Width: 0.060 inches Maximum Power Dissipation Rating: 2.50 watts Ambient Tempurature At Full Rated Power: 25.0 degrees celsius Maximum Operating Temp: 125.0 degrees celsius Mount Of Measure: No Fig:		
And a second sec		
Style Designator:   Disk   Terminal Type And Quantity:   2 wire lead   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:   No   Fig:		
2.50 watts Ambient Tempurature At Full Rated Power: 25.0 degrees celsius Maximum Operating Temp: 125.0 degrees celsius Thermal Time Constant In Seconds: 80.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 20.0 Inclosure Type: Encapsulated Zero Power Resistance: 5.240 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0 Style Designator: Disk Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Ма	ximum Power Dissipation Rating:
25.0 degrees celsius Maximum Operating Temp: 125.0 degrees celsius Thermal Time Constant In Seconds: 80.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 20.0 Inclosure Type: Encapsulated Zero Power Resistance: 5.240 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0 Style Designator: Disk Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:		
Maximum Operating Temp: 125.0 degrees celsius Thermal Time Constant In Seconds: 80.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 20.0 Inclosure Type: Encapsulated Zero Power Resistance: 5.240 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0 Style Designator: Disk Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	An	nbient Tempurature At Full Rated Power:
125.0 degrees celsius Thermal Time Constant In Seconds: 80.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 20.0 Inclosure Type: Encapsulated Zero Power Resistance: 5.240 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0 Style Designator: Disk Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	25.	0 degrees celsius
Thermal Time Constant In Seconds: 80.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 20.0 Inclosure Type: Encapsulated Zero Power Resistance: 5.240 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0 Style Designator: Disk Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Ма	ximum Operating Temp:
80.0 Power Dissipation Constant In Milliwatts Per Deg Celsius: 20.0 Inclosure Type: Encapsulated Zero Power Resistance: 5.240 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0 Style Designator: -10.0/+10.0 Style Designator: -10.0 Style Itife: N/a Unit Of Measure: Demilitarization: No Fig:	12	5.0 degrees celsius
Power Dissipation Constant In Milliwatts Per Deg Celsius: 20.0 Inclosure Type: Encapsulated Zero Power Resistance: 5.240 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0 Style Designator: Disk Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Th	ermal Time Constant In Seconds:
20.0 Inclosure Type: Encapsulated Zero Power Resistance: 5.240 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0 Style Designator: -10.0/+10.0 Style Designator: Disk Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	80.	0
Inclosure Type: Encapsulated Zero Power Resistance: 5.240 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0 Style Designator: -10.0/+10.0 Style Designator: Disk Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Po	wer Dissipation Constant In Milliwatts Per Deg Celsius:
Encapsulated Zero Power Resistance: 5.240 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0 Style Designator: Disk Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No	20.	0
Zero Power Resistance: 5.240 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0 Style Designator: Disk Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Inc	losure Type:
5.240 kilohms Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0 Style Designator: Disk Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No	En	capsulated
Zero Power Resistance Tolerance In Percent At Reference Temp: -10.0/+10.0 Style Designator: Disk Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fig:	Zei	ro Power Resistance:
-10.0/+10.0 Style Designator: Disk Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	5.2	40 kilohms
Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	Ze	ro Power Resistance Tolerance In Percent At Reference Temp:
Disk Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-10	0.0/+10.0
Terminal Type And Quantity: 2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:	-	-
2 wire lead Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:		
Shelf Life: N/a Unit Of Measure:  Demilitarization: No Fiig:		
N/a Unit Of Measure:  Demilitarization: No Fiig:		
Unit Of Measure:  Demilitarization: No Fiig:		
 Demilitarization: No Fiig:		
No Fiig:	Un	it Of Measure:
No Fiig:		
Fiig:		
-		
A086a0		-