

View Online at <https://aerobasegroup.com/nsn/5905-00-925-2847>

**Section Quantity:**

1

**Body Style:**

Rectangular w/pointer adjustment

**Reliability Indicator:**

Not established

**Terminal Length:**

Between 0.490 inches and 0.510 inches

**Body Length:**

0.312 inches

**Body Width:**

Between 0.490 inches and 0.510 inches

**Body Height:**

0.562 inches

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

320.0

**Maximum Starting Torque:**

7.50 inch-ounces

**Maximum Running Torque:**

7.50 inch-ounces

**Center To Center Distance Between Terminals:**

Between 0.190 inches and 0.210 inches

**Terminal Location:**

Lower adjacent side two rows

**Mounting Method:**

Terminal

**Center To Center Distance Between Terminal Rows:**

Between 0.090 inches and 0.110 inches

**Electrical Resistance Per Section:**

2.0 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

320.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

Between 0.090 inches and 0.110 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Actuator Travel Control Feature:**

Stops

**Temperature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:**

-20.0/+20.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

50.0 single section

**Standard Taper Curve Per Section:**

A single section

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0