NSN 5905-00-925-7381

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-925-7381

| Section Quantity: |
|---|
| 1 |
| Body Style: |
| Rectangular w/pointer adjustment |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.187 inches |
| Body Length: |
| 0.250 inches |
| Body Width: |
| 0.312 inches |
| Body Height: |
| 0.370 inches |
| Actuator Type: |
| Flush drive with slot-hole |
| Effective Electrical Rotation In Deg Angular Rotation: |
| 280.0 |
| Maximum Starting Torque: |
| 5.00 inch-ounces |
| Maximum Running Torque: |
| 5.00 inch-ounces |
| Maximum Stop Torque: |
| 6.00 inch-ounces |
| Center To Center Distance Between Terminals: |
| Between 0.180 inches and 0.220 inches |
| Terminal Location: |
| Right adjacent side two rows |
| Mounting Method: |
| Terminal |
| Center To Center Distance Between Terminal Rows: |
| 0.100 inches |
| Electrical Resistance Per Section: |
| 5.0 kilohms single section |
| Rotary Actuator Travel In Angular Deg: |
| 300.0 |
| Center To Center Distance Between Center Terminal And Outside Terminal: |
| Between 0.090 inches and 0.110 inches |
| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
| 150.0 single section |

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0/+70.0 single section

NSN 5905-00-925-7381

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



| Power Dissipation Rating Per Section In Watts: |
|---|
| 0.5 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -5.0/+5.0 single section |
| Actuator Travel Control Feature: |
| Stops |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Standard Taper Curve Per Section: |
| A single section |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |