## NSN 5905-00-925-8744

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-925-8744 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.006 inches **Overall Height:** 0.360 inches **Overall Width:** Between 0.270 inches and 0.290 inches **Mounting Hole Diameter:** 0.088 inches **Shaft Diameter:** Between 0.090 inches and 0.110 inches **Shaft Length:** Between 0.270 inches and 0.290 inches **Body Length:** 1.000 inches **Body Width:** Between 0.270 inches and 0.290 inches **Body Height:** 0.310 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Maximum Starting Torque:** 8.00 inch-ounces **Lateral Distance Between Mounting Hole Centers:** Between 0.825 inches and 0.835 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Lower adjacent side single row **Mounting Method:** Unthreaded hole **Features Provided:** 

Nonmetallic shaft

**Electrical Resistance Per Section:** 

2.0 kilohms single section

## NSN 5905-00-925-8744

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
5400.0
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Clutch
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A002a0