

View Online at <https://aerobasegroup.com/nsn/5905-00-925-9313>

Section Quantity:

1

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

Between 1.031 inches and 1.157 inches

Body Diameter:

Between 0.594 inches and 0.656 inches

Shaft Diameter:

Between 0.125 inches and 0.127 inches

Shaft Length:

Between 0.593 inches and 0.657 inches

Mounting Bushing Length:

Between 0.359 inches and 0.391 inches

Body Length:

Between 0.438 inches and 0.500 inches

Overall Diameter:

0.907 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 297.0 and 303.0

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

Between 0.218 inches and 0.250 inches

Screw Thread Diameter:

0.250 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

100.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 297.0 and 303.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

85.0 single section

Power Dissipation Rating Per Section In Watts:

0.2 free air single section

Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0