NSN 5905-00-926-0364

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-926-0364

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -20.0/+20.0 Electrical Resistance: 1.100 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0	
Electrical Resistance: 1.100 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0	
1.100 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0	
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0	
-1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0	
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0	
125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 350.0	
350.0	
Tempurature Range Of Tempurature Coefficient In Deg Celsius:	
-55.0/+350.0	
Inclosure Method:	
Encapsulated	
Terminal Type:	
Wire lead	
Reliability Indicator:	
Not established	
Body Diameter:	
0.188 inches	
Body Length:	
0.375 inches	
Power Dissipation Rating In Watts:	
1.000 free air	
Style Designator:	
Axial terminal each end	
Test Data Document:	
99971-7736734 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification for	rmat
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environment	:al
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A001a0	