NSN 5905-00-926-0405

Section Quantity:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

Body Style:

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-926-0405

2.000 inches
Body Diameter:
1.625 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
1.125 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Nonturn Device Location:
At 12 oclock
Nonturn Device Radius:
0.500 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Mounting Facility Quantity:
2
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
40.0 ohms single section
Power Dissipation Rating Per Section In Watts:
25.0 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section

NSN 5905-00-926-0405

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0