NSN 5905-00-926-2858

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-926-2858 **Section Quantity:** 1 **Body Style:** Cylindrical servo mounted **Reliability Indicator:** Not established **Pilot Diameter:** Between 1.9350 inches and 1.9370 inches Pilot Length: Between 0.0270 inches and 0.0320 inches **Overall Length:** 1.218 inches **Undercut Diameter:** 1.9375 inches **Undercut Width:** 0.0310 inches **Body Diameter:** Between 1.995 inches and 2.005 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 0.219 inches **Body Length:** Between 0.963 inches and 0.973 inches **Overall Diameter:** 2.406 inches **Mounting Lip Diameter:** Between 1.9950 inches and 2.0050 inches **Mounting Lip Depth:** 0.0310 inches **Shaft Style:** Round **Shaft Bearing Type:** Ball **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 350.0 **Maximum Starting Torque:**

0.60 inch-ounces

Shaft End Play:

0.0005 inches

NSN 5905-00-926-2858

Precision Wire Wound Variable Resistor - Page 2 of 2



Terminal Location: Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 50.0 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 **Function Conformity Tolerance Per Section:** -0.50/+0.50 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 80.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -150.0/+150.0 single section **Power Dissipation Rating Per Section In Watts:** 4.0 free air single section **Function Conformity Per Section:** Single section independent linearity **Fixed Tap Quantity Per Section:** 1 single section **Tap Location Tolerance Per Section:** -2.0/+2.0 ohms single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section **Actuator Travel Control Feature:** Continuous motion **Tap Location From Ccw Terminal Per Section In Ohms:** 25000.0 single section **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 25.0 single section **Special Features:** Dog drive type coupling included **Terminal Type And Quantity:** 8 tab, solder lug Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A002a0