NSN 5905-00-926-8799

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-926-8799

| -20.0/+20.0 Electrical Resistance: 40.200 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: 06481-900641 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
|--|
| 40.200 ohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Ambient Tempurature In Deg Celsius At Full Rated Power: 25.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 275.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+275.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Wire lead Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Reliability Indicator: Not established Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Not established Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Body Diameter: 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| 0.187 inches Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Body Length: 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| 0.703 inches Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Power Dissipation Rating In Watts: 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| 4.000 free air Style Designator: Axial terminal each end Test Data Document: |
| Style Designator: Axial terminal each end Test Data Document: |
| Axial terminal each end Test Data Document: |
| Test Data Document: |
| |
| 06481-900641 specification (includes engineering type hulletins, brochures, etc., that reflect specification type data in specification formati |
| ooto i oooot i opoomoation (moiddes engineening type bulletins, broondres, etc., that rehect specification type data in specification format, |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A001a0 |