NSN 5905-00-927-0797

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-927-0797

Section Quantity: Body Style: Cylindrical **Reliability Indicator:** Not established **Overall Length:** 0.467 inches **Terminal Length:** Between 0.142 inches and 0.172 inches **Body Diameter:** Between 0.285 inches and 0.295 inches **Body Length:** Between 0.305 inches and 0.315 inches **Overall Diameter:** Between 0.285 inches and 0.295 inches **Actuator Type:** Flush drive with slot-hole **Effective Electrical Rotation In Deg Angular Rotation:** 290.0 **Center To Center Distance Between Terminals:** 0.200 inches **Terminal Location:** Rear end **Mounting Method: Terminal Electrical Resistance Per Section:** 20.0 ohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 Center To Center Distance Between Center Terminal And Outside Terminal: Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 105.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -20.0/+20.0 single section **Power Dissipation Rating Per Section In Watts:** 0.25 free air single section **Resistance Tolerance Per Section In Percent:** -10.0/+10.0 single section

Actuator Travel Control Feature:

Continuous motion

NSN 5905-00-927-0797

Fiig: A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Nο