

View Online at <https://aerobasegroup.com/nsn/5905-00-927-2822>

Section Quantity:

1

Body Style:

Rectangular w/bushing

Reliability Indicator:

Not established

Overall Length:

Between 1.275 inches and 1.345 inches

Overall Height:

Between 0.292 inches and 0.332 inches

Overall Width:

Between 0.292 inches and 0.332 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.250 inches

Mounting Bushing Length:

0.188 inches

Body Length:

Between 1.040 inches and 1.080 inches

Body Width:

Between 0.292 inches and 0.332 inches

Body Height:

Between 0.292 inches and 0.332 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Fragility Factor:

Moderately rugged

Screw Thread Diameter:

0.216 inches

Screw Thread Series Designator:

Unf

Screw Thready Qty Per Inch (tpi):

28.0

Terminal Location:

Rear end

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

1.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

3600.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-50.0/+50.0 single section

Power Dissipation Rating Per Section In Watts:

1.5 free air single section

Resistance Tolerance Per Section In Percent:

-5.0/+5.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Precious Material And Location:

Terminals gold

Precious Material:

Gold

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0