

View Online at <https://aerobasegroup.com/nsn/5905-00-927-5068>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

2.391 inches

Body Diameter:

0.922 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.250 inches

Mounting Bushing Length:

0.375 inches

Body Length:

1.141 inches

Overall Diameter:

1.563 inches

Undercut Diameter:

0.125 inches

Shaft Style:

Round, stepped

Shaft Bearing Type:

Sleeve

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Maximum Starting Torque:

6.00 inch-ounces

Maximum Running Torque:

6.00 inch-ounces

Maximum Stop Torque:

196.00 inch-ounces

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

0.438 inches

Undercut Length:

0.375 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

250.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

105.0 all sections

Power Dissipation Rating Per Section In Watts:

0.56 7th secondary finish

Resistance Tolerance Per Section In Percent:

-20.0/+20.0 2nd section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

40.0 all sections

Standard Taper Curve Per Section:

C 1st section

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0