NSN 5905-00-927-5071

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-927-5071

view Offilite at https://defobasegroup.com/hsi//5505-00-527-507 h
Section Quantity:
1
Body Style:
Cylindrical
Reliability Indicator:
Not established
Overall Length:
0.525 inches
Body Diameter:
0.630 inches
Body Length:
0.328 inches
Overall Diameter:
0.630 inches
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
260.0
End Application:
1emory s. Land class as; oliver perry class ffg; forrestal class cv; spruance class dd (963); tarawa class lha; sturgeon class ssn (637);
wasp class lhd; nimitz class cvn; austin ship class lpd-4 amphibious transport docks; iwo jima class lph
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
2.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
260.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
85.0 single section
Power Dissipation Rating Per Section In Watts:
0.2 free air single section
Resistance Tolerance Per Section In Percent:
-20.0/+20.0 single section
Actuator Travel Control Feature:
Stops
Criticality Code Justification:
Feat
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section

A single section

Standard Taper Curve Per Section:

NSN 5905-00-927-5071

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Special Features:
Weapon system essential
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0