Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-927-6495

### Section Quantity:

1

Body Style:

Cylindrical bushing mounted

# **Reliability Indicator:**

Not established

### **Overall Length:**

1.126 inches

#### **Body Diameter:**

0.500 inches

### Shaft Diameter:

0.125 inches

Shaft Length:

#### 0.438 inches

### Mounting Bushing Length:

# 0.250 inches

**Body Length:** 

0.453 inches

### Overall Diameter:

0.500 inches

## Shaft Style:

Round, slotted

#### Actuator Type:

Single shaft

## Nonturn Device Radius:

0.245 inches

## Screw Thread Diameter:

0.250 inches

## Screw Thread Series Designator:

Unef

# Screw Thready Qty Per Inch (tpi):

32.0

# Terminal Location:

Rear end

# Mounting Method:

Locking bushing

# **Electrical Resistance Per Section:**

2.0 ohms single section

# Power Dissipation Rating Per Section In Watts:

0.5 free air single section

# Resistance Tolerance Per Section In Percent:

-10.0/+10.0 single section

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



### Standard Taper Curve Per Section:

A single section

#### **Test Data Document:**

10001-1412520-6 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0