NSN 5905-00-928-1048

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-928-1048

Electrical Resistance: 39,000 ohms Resistance Tolerance in Percent: 0,100/40,100 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: 65.0/4145.0 Tempurat	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 0.1001/-0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: 6. Incapsulated Forminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter: 0.250 inches 30dy Length: 0.312 inches Power Dissipation Rating In Watts: 1.125 free air Skyle Designator: xxixal terminals one end Fest Data Document: 11349-milr33/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: Via Jint Of Measure:	-20.0/+20.0
Resistance Tolerance In Percent: 0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Fempurature Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established 30dy Diameter: 9.250 inches 30dy Length: 9.312 inches Power Dissipation Rating In Watts: 9.125 free air Style Designator: Axial terminals one end Fest Data Document: 9.1418 personal Commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Juint Of Measure:	Electrical Resistance:
0.100/+0.100 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Vot established 38ody Diameter: 1,250 inches 38ody Length: 1,312 inches 29ower Dissipation Rating In Watts: 1,312 inches 29ower Dissipation Rating In Watts: 1,3149 inmit/33/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Vota Jint Of Measure:	69.000 ohms
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Rempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 1.250 inches Body Length: 1.312 inches Power Dissipation Rating In Watts: 1.125 free air Style Designator: Xival teminals one end Feet Data Document: 194349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Valuation Measure: Joint Of Measure: Joint Office: Joint	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 156.0/+145.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established 3ody Diameter: 1.250 inches 3ody Length: 2.312 inches Power Dissipation Rating In Watts: 1.25 free air Style Designator: Xxial terminals one end Test Data Document: 18149-milrg3/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: Va Juit Of Measure: - Demilitarization: No	-0.100/+0.100
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/4145.0 Tempurature Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 10.250 inches Body Length: 1.312 inches Power Dissipation Rating In Watts: 1.25 free air Style Designator: Axial terminals one end Test Data Document: 181349-miliga3/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Shelf Life: Va Joint Of Measure: - Demilitarization: No	Ambient Tempurature In Deg Celsius At Full Rated Power:
Pempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 nclosure Method: Encapsulated Perminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: xixial terminals one end Pest Data Document: 91349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: - Demilitarization: No Filig:	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 65.0/+145.0 nclosure Method: 6.ncapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Fest Data Document: 81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: - Demilitarization: No Figig:	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches 30dy Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Xxial terminals one end Fest Data Document: 81349-militg3//20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: V/a Jnit Of Measure: - Demilitarization: No Filig:	145.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Fest Data Document: 81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Juit Of Measure: - Demilitarization: No Filig:	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Nire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Fest Data Document: B1349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Via Unit Of Measure: Demilitarization: No Piig:	-65.0/+145.0
Ferminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Fest Data Document: 81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Sheff Life: Via Unit Of Measure: Demilitarization: No Periligi:	Inclosure Method:
Are lead Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Avial terminals one end Fest Data Document: 81349-millr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Juit Of Measure: - Demilitarization: No Signature Power Dissipation Po	Encapsulated
Reliability Indicator: Not established Body Diameter: 0.250 inches Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Byte Designator: Axial terminals one end Fest Data Document: 81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: - Demilitarization: No Signature Power Dissipation No Signature Power Dissipation No String:	Terminal Type:
Note established Body Diameter: Diagony Diameter: Diagony Diameter: Diagony Length: Di	Wire lead
Body Length: D. 250 inches Body Length: D. 312 inches Power Dissipation Rating In Watts: D. 125 free air Style Designator: Avail terminals one end Fest Data Document: B1349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: No Dinit Of Measure: Demilitarization: No Signification type data in specification format; "average", "", etc.).	Reliability Indicator:
2.250 inches 3.30dy Length: 2.312 inches 2.312 inches 2.312 inches 2.312 inches 2.313 inches 2.314 inches 2.315 free air 3.314 brain als one end 3.315 post Data Document: 3.3149-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). 3.3141 public of Measure: 3.3142	Not established
Body Length: 0.312 inches Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Fest Data Document: 81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: Wa Unit Of Measure: Demilitarization: No	Body Diameter:
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Fest Data Document: 81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Junit Of Measure: - Demilitarization: No	0.250 inches
Power Dissipation Rating In Watts: 0.125 free air Style Designator: Axial terminals one end Fest Data Document: 81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: - Demilitarization: No	Body Length:
Out 25 free air Style Designator: Axial terminals one end Fest Data Document: B1349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: - Demilitarization: No Filig:	0.312 inches
Style Designator: Axial terminals one end Fest Data Document: 31349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Power Dissipation Rating In Watts:
Axial terminals one end Fest Data Document: 81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.125 free air
Fest Data Document: 81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). 8helf Life: N/a Jnit Of Measure: - Demilitarization: No Filig:	Style Designator:
81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Axial terminals one end
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Test Data Document:
and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	81349-milr93/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
Shelf Life: N/a Jnit Of Measure: - Demilitarization: No Fiig:	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
N/a Jnit Of Measure: - Demilitarization: No Fiig:	and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Jnit Of Measure: - Demilitarization: No Fiig:	Shelf Life:
- Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Filg:	Demilitarization:
	No
\004-0	Fiig:
AUUTAU	A001a0