Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-928-1198

# Section Quantity:

1

Body Style:

Rectangular

# **Reliability Indicator:**

Not established

### **Terminal Length:**

0.187 inches

#### Shaft Diameter:

0.100 inches

#### Shaft Length:

0.200 inches

#### **Body Length:**

0.375 inches

#### **Body Width:**

0.255 inches

# Body Height:

0.317 inches

# Shaft Style:

Round, slotted

# Actuator Type:

Single shaft

### Effective Electrical Rotation In Deg Angular Rotation:

300.0

### **Center To Center Distance Between Terminals:**

0.200 inches

#### **Terminal Location:**

Right adjacent side two rows

#### **Mounting Method:**

Terminal

# Center To Center Distance Between Terminal Rows:

0.100 inches

# **Electrical Resistance Per Section:**

100.0 ohms single section

# Rotary Actuator Travel In Angular Deg:

280.0

# Center To Center Distance Between Center Terminal And Outside Terminal:

### 0.100 inches

### Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

### Power Dissipation Rating Per Section In Watts:

0.5 free air single section



## **Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

### Actuator Travel Control Feature:

Stops

## Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

55.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A002a0