NSN 5905-00-928-1220

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-00-928-1220 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.282 inches **Body Diameter:** 0.938 inches **Shaft Diameter:** Between 0.248 inches and 0.250 inches **Shaft Length:** 0.813 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 0.469 inches **Overall Diameter:** 1.250 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Nonturn Device Location:** At 9 oclock **Nonturn Device Radius:** Between 0.422 inches and 0.454 inches **Screw Thread Diameter:** 0.375 inches Radially positioned over less than half the circumference

Screw Thread Series Designator: Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location: Mounting Method:** Standard bushing **Electrical Resistance Per Section:** 500.0 ohms single section **Power Dissipation Rating Per Section In Watts:** 5.0 free air single section

NSN 5905-00-928-1220

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



-10.0/+10.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0