Nonprecision Wire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-00-928-2982

Section Quantity: 1 **Body Style:** Rectangular w/mounting holes/slots **Reliability Indicator:** Not established **Overall Length:** 1.050 inches **Overall Height:** Between 0.295 inches and 0.335 inches **Overall Width:** Between 0.170 inches and 0.190 inches **Mounting Hole Diameter:** Between 0.088 inches and 0.098 inches Shaft Diameter: Between 0.100 inches and 0.130 inches Shaft Length: Between 0.035 inches and 0.065 inches **Body Length:** Between 0.990 inches and 1.010 inches **Body Width:** Between 0.170 inches and 0.190 inches **Body Height:** Between 0.295 inches and 0.335 inches Shaft Style: Round, slotted Actuator Type: Single shaft Lateral Distance Between Mounting Hole Centers: Between 0.745 inches and 0.755 inches **Mounting Facility Quantity:** 2 **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Electrical Resistance Per Section:** 10.0 kilohms single section **Power Dissipation Rating Per Section In Watts:** 0.8 free air single section **Resistance Tolerance Per Section In Percent:** -5.0/+5.0 single section

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0