NSN 5905-00-928-5313

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-928-5313

Electrical Resistance: 1,550 kilohms Resistance Tolerance In Percent: 0,030/40,030 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1,000 inches 1,304 Diameter: 1,141 inches 1,309 Diameter: 1,319 inches 1,309 Diameter: 1,310 free air Style Designator: Xival terminal each end Test Data Document: 16481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 1,424 Lines 1,424 Lines L	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Resistance Tolerance In Percent: 0.030/+0.030 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches 300y Diameter: 1.41 inches 300y Length: 1.391 inches Power Dissipation Rating In Watts: 1.010 free air Style Designator: Avail terminal each end Test Data Document: 106481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 1xixcludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via	-10.0/+10.0
Resistance Tolerance In Percent: 0.030/40.030 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Vot established Terminal Length: 1.000 inches 30dy Diameter: 1.141 inches 30dy Length: 3.391 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: vixial terminal each end Test Data Document: 18481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing; etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing; etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing; etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)	Electrical Resistance:
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 156.0/+125.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 156.0/+125.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 156.0/+125.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+125.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+125.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+125.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+125.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+125.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+125.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+125.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+125.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+125.0 Fernpurature Range Of Tempurature Coefficient In Deg Celsius: 150.0/+125.0 Fernpurature Range Of Tempurature Range Of T	4.550 kilohms
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 155.0/+125.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: I.000 inches 30dy Diameter: I.141 inches 30dy Length: I.391 inches Power Dissipation Rating In Watts: I.151 Evest Data Document: Ixial terminal equipment manufacturer drawing, etc.; Ixial terminal expecification, standard or other document that may be referenced in a basic governing drawing) Ixial terminal expecification, standard or other document that may be referenced in a basic governing drawing)	Resistance Tolerance In Percent:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0+125.0 Inclosure Method: Incapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.000 inches 80dy Diameter: 1.041 inches 30dy Length: 1.391 inches Power Dissipation Rating In Watts: Not office air Style Designator: Exist a Bata Document: 1.0481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via	-0.030/+0.030
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 45.0 Fempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches 8.0dy Diameter: 1.411 inches 8.0dy Diameter: 1.411 inches 8.0dy Length: 1.391 inches Power Dissipation Rating In Watts: 1.010 free air 8.141 Document: 8.142 Document: 8.143 Document: 8.144 Document: 8.145 Document: 8.145 Document: 8.146 Document: 8.145 Document: 8.146 Document: 8.146 Document: 8.146 Document: 8.147 Document: 8.148 Document: 8.149 Document: 8.149 Document: 8.140 Document: 8.140 Document: 8.140 Document: 8.140 Document: 8.140 Document: 8.141 Document: 8.140 Document: 8.141 Document: 8.140 Document: 8.141 Document: 8.141 Document: 8.142 Document: 8.143 Document: 8.144 Document: 8.145 Doc	Ambient Tempurature In Deg Celsius At Full Rated Power:
As a contractor of a contracto	125.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/+125.0 Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches Body Diameter: 1.141 inches Body Length: 1.391 inches Power Dissipation Rating In Watts: 1.000 free air Style Designator: Axial terminal each end Fest Data Document: 1.6481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: 1.42	Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
nclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches Rody Diameter: 1.141 inches Rody Length: 1.031 inches Rody Length: 1.0391 inches Rody Length: 1.0481 inches Rody Length: 1.050 free air Roty Length: 1.050 free air Roty Length: 1.050 free air Roty Length: 1.051 Aurilla terminal each end Rest Data Document: 1.06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 1.051 Excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: 1.44	145.0
Inclosure Method: Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches 8.0dy Diameter: 2.141 inches 8.0dy Length: 2.391 inches Power Dissipation Rating In Watts: 2.100 free air Style Designator: Axial terminal each end Fest Data Document: 106481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2.50cludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	Tempurature Range Of Tempurature Coefficient In Deg Celsius:
Encapsulated Ferminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches 2.0dy Diameter: 2.141 inches 2.0dy Length: 2.391 inches Power Dissipation Rating In Watts: 2.100 free air Style Designator: Axial terminal each end Fest Data Document: 1.6481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2.54cc designation, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa	-55.0/+125.0
Terminal Type: Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches Rediability Indicator: Responsible to the state of the state	Inclosure Method:
Wire lead Reliability Indicator: Not established Ferminal Length: 1.000 inches Rody Diameter: 0.141 inches Rody Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Encapsulated
Reliability Indicator: Not established Ferminal Length: 1.000 inches Redy Diameter: 1.0.141 inches Redy Length: 1.0.391 inches Power Dissipation Rating In Watts: 1.0.100 free air Retyle Designator: 1.0.101 free besignator: 1.0.102 Axial terminal each end 1.0.103 Test Data Document: 1.0.106481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 1.0.103 Executed any specification, standard or other document that may be referenced in a basic governing drawing) 1.0.104 Shelf Life: 1.0.105 Test Data Document drawing drawing be referenced in a basic governing drawing) 1.0.105 Test Data Document drawing drawing be referenced in a basic governing drawing) 1.0.105 Test Data Document drawing drawi	Terminal Type:
Note established Ferminal Length: 1.000 inches Body Diameter: 1.141 inches Body Length: 1.0391 inches Power Dissipation Rating In Watts: 1.100 free air Style Designator: 1.101 Axial terminal each end Fest Data Document: 1.106481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 1.101 excludes any specification, standard or other document that may be referenced in a basic governing drawing) 1.102 Shelf Life: 1.103	Wire lead
Ferminal Length: 1.000 inches 3ody Diameter: 2.141 inches 3ody Length: 2.391 inches 2.09wer Dissipation Rating In Watts: 2.100 free air 3tyle Designator: Axial terminal each end Fest Data Document: 2.6481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2.excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: 1.000 inches 3.000 piameter: 3.010 free air 3.010 fr	Reliability Indicator:
Body Diameter: 0.141 inches Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Byle Designator: Axial terminal each end Fest Data Document: 0.6481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a	Not established
Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a	Terminal Length:
2.141 inches Body Length: 2.391 inches Power Dissipation Rating In Watts: 2.100 free air Style Designator: Axial terminal each end Fest Data Document: 2.106481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; 2.20cc excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	1.000 inches
Body Length: 0.391 inches Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Body Diameter:
Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 0.6481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:	0.141 inches
Power Dissipation Rating In Watts: 0.100 free air Style Designator: Axial terminal each end Fest Data Document: 0.6481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Body Length:
O.100 free air Style Designator: Axial terminal each end Fest Data Document: O6481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:	0.391 inches
Axial terminal each end Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:	Power Dissipation Rating In Watts:
Axial terminal each end Fest Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:	0.100 free air
Test Data Document: 06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life:	Style Designator:
06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Axial terminal each end
excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a	Test Data Document:
Shelf Life: N/a	06481-900532 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;
N/a	excludes any specification, standard or other document that may be referenced in a basic governing drawing)
	Shelf Life:
Jnit Of Measure:	N/a
	Unit Of Measure:
-	
Demilitarization:	Demilitarization:
10	No
Filg:	Fiig:
A001a0	A001a0