NSN 5905-00-928-7975

Noninductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-00-928-7975

-10,04-10.0 Electrical Resistance: 12,500 kilohms Resistance Tolerance in Percent: -0.250/4-0.250 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Even Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -0.256.0/4-125.0 Intelosure Method: -0.256.0 In	Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
Electrical Resistance: 12.500 kilohms Resistance Tolerance in Percent:	
12.500 kilohms Resistance Tolerance in Percent: -0.250/40.250 Ambient Tempurature in Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature in Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient in Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.275 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: Basil-Be-Ge00011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-6600011771 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-6600011771 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) District Company of the desired of the document that may be referenced in a basic governing drawing) Body District Company of the document of the document that may be referenced in a basic governing drawing).	
Resistance Tolerance In Percent: -0.250/+0.250 Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Note established Body Diameter: 0.275 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Dosignator: Axial terminals one end Test Data Document: 88818-6600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-6600011711 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-6600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-6600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) shelf Life: N/a Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/±125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.275 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, original equipment manufacturer drawing, sheefficients, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) shelf-Life: Na Unit Of Measure: - Demilitarization: No	
Ambient Tempurature In Deg Celsius At Full Rated Power: 125.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.275 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing.) Shelf Life: Na Unit Of Measure:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: 55.0/4125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.275 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: B88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: — Demilitarization: No Filig:	
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 145.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.275 inches Body Length: 0.375 inches Power Dissipation Rating in Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-6600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-660011711 drawing (this is the basic governing drawing, original equipment manufacturer drawing, specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing. Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.275 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 8818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+125.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.275 inches Body Length: 0.375 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Fiig:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.275 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Unit Of Measure: Demilitarization: No Flig:	
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.275 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-6600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.275 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Terminal Type: Wire lead Reliability Indicator: Not established Body Diameter: 0.275 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-6600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	
Wire lead Reliability Indicator: Not established Body Diameter: 0.275 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-6600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-600011711 drawing (this is the basic governing drawing, such as a contractor drawing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Reliability Indicator: Not established Body Diameter: 0.275 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Note established Body Diameter: 0.275 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Body Diameter: 0.275 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
0.275 inches Body Length: 0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
0.375 inches Power Dissipation Rating In Watts: 0.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Body Length:
O.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
O.250 free air Style Designator: Axial terminals one end Test Data Document: 88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Power Dissipation Rating In Watts:
Axial terminals one end Test Data Document: 88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.250 free air
Test Data Document: 88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Axial terminals one end
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c600011711 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Test Data Document:
drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	88818-c600011500 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 88818-c60001171
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any
N/a Unit Of Measure: Demilitarization: No Fiig:	specification, standard or other document that may be referenced in a basic governing drawing)
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A001a0	Fiig:
	A001a0